

CINEMA SERIES – C520



System Features

- 5-axis advanced fiber optic gyro-stabilization
- VectorSteering look-down capability with no gimbal lock
- Interchangeable cameras/lenses/inner-axis in less than 30 minutes
- Stabilized or steerable horizon with in-flight automatic calibration
- High-speed fiber optic video data transfer
- No ITAR or EAR export restrictions
- Modularized to ship as excess baggage (<70lbs/32kg per case)
- MIL-STD-810F power filters with reverse polarity protection
- Independent Structural Analysis IAW FAA 14 CFR 23.337, 25.337, 27.337, & 29.337 at 200 knots
- Engineered/Manufactured to DO-160G standards - not certified
- Platform designed for both standard and inverted use
- Wireless capability option
- Metadata outputs (lens, camera, & GPS functions)
- Geo-pointing option
- No auxiliary junction unit required
- Electro-mechanical gimbal stow mechanism
- Compatible with existing air and ground mounts
- Standard 2-year warranty and 24/7/365 customer service

System Specs

Gimbal Performance

5-axis advanced fiber optic gyro-stabilization
Azimuth: 360° continuous
Elevation: 30° to -205° from horizontal
Roll: +/- 120° (steerable/stabilized)
Gimbal Slew Rate: 0-150°/second
Max Operational Airspeed: 200 knots - certified to FAA 14CFR requirements, increased airspeeds possible

Interface

Control: RS-232, RS-422, or ethernet

Electrical

VIN: 18-33 VDC
Power: 15 amps max draw at 28 VDC

Dimensions

Gimbal width: 20 inches (508 mm)
Gimbal height: 23.5 inches (597 mm)
Snout length: 0-6 inches (0-152 mm)
Cable set length: 20 - 100 feet

Weight

Platform: 85 lbs (38.5 kg) + payload
Laptop control unit: 7 lbs (3.2 kg)
Auxiliary junction unit: payload specific
Cable set: 8 lbs (3.6 kg)

Environmental

Operating temperature: -4° to +122°F (-20° to +50°C)
Sealed system for airborne/ground/marine applications

Interchangeable Camera Options

Sony PMW-F55, HDC-2500 & P1
RED Dragon, RED Weapon
Arri Alexa XT M, Arri Alexa Mini
*Other cameras available upon request

Interchangeable Lens Options

Angenieux Optimo Series, including 12:1
Canon Cinema Series
Fujinon Premiere PL/Cabrio Series
B4 mount ENG lenses (limited to payload compatibility)
*Other lenses available upon request

Recommended Helicopter Mount Configuration

Airfilm AS 350/355 AFSP Nose Mount
Airfilm Bell 206/206L/407 Nose Camera Mount
Airfilm 6-axis passive vibration isolator
*Compatible with various other mounts

Recommended Vehicle/Marine Mount Configuration

Airfilm Unimount
Airfilm 6-axis passive vibration isolator

*Specifications are subject to change

CINEMA SERIES – C520 CAMERA & LENS CONFIGURATIONS

	Angenieux Optimo 28-340	Angenieux Optimo 24-290	Angenieux Optimo Style 25-250	Angenieux Optimo 19.5-94	Arri Ultra Wide Zoom UWZ 9.5-18	Canon 50-1000	Canon 30-300	Canon 17-120	Canon 14.5-60	Fujinon Cabrio 25-300	Fujinon Cabrio 19-90	Zeiss Master Primes (14 thru 100)	Canon 40x10	Canon 40x14	Canon 14x4.3	Fujinon 42x9.7	Fujinon 42x13.5	Fujinon 14x4.5	
Arri Alexa XT M	140	140	120	115	115	115	115	115	115	135	115	115	115	115	115	115	115	115	115
Arri Alexa Mini	140	140	120	115	115	115	115	115	115	135	115	115	115	115	115	115	115	115	115
Canon C500	140	140	120	115	115	115	115	115	115	135	115	115	115	115	115	115	115	115	115
Red Epic MX/Dragon	140	140	120	115	115	115	115	115	115	135	115	115	115	115	115	115	115	115	115
Red Weapon	140	140	120	115	115	115	115	115	115	135	115	115	115	115	115	115	115	115	115
Sony F55 with Recorder	140	140	120	115	115	115	115	115	115	135	115	115	115	115	115	115	115	115	115
Sony F55 without Recorder	140	140	120	115	115	115	115	115	115	135	115	115	115	115	115	115	115	115	115
Sony 2500 with T-Block													115	115	115	115	115	115	115
Sony 2500 repackaged													115	115	115	115	115	115	115
Sony P1													115	115	115	115	115	115	115

Outlined payload configurations use the I/BE HDx35 B4/PL Adapter

All weights shown in pounds

All GSS C520 payload configurations are qualified to fly on the Airfilm AS350/355 AFSP Nose Mount

Most GSS C520 payload configurations are qualified to fly on the Bell 206/206L/407 Nose Camera Mount

All GSS C520 payload configurations fly as excess baggage in cases at less than 70lbs/32kg

The GSS C520 has more camera and lens payload configurations than any system in its' class. Many other options are available upon request